

## ALL-IN-ONE ultra compact joint for 1 core polymeric insulated cable with sheath for mechanical protection.

### ARE4(P1)H5(AR)E(X) e (A)RG7(E4)H1(AR)E(X)

The kit consists of a single cold shrinkable compact and short body with all components (stress control, insulating, semiconductive, metallic shielding, and outer protection) pre-assembled onto one removable support, which allows a rapid and easy installation of the joint. The use of solder or other devices for connection of the metallic shield is not required. Mechanical connector included in the kit.

Compliant with standards  
CENELEC HD 629.1 S2, CEI 20-62/1



List of available kits. Mechanical locking connector included.

Famiglia Prodotti Type	Tensioni Voltage U <sub>0</sub> /U/U <sub>max</sub> [kV]	Sezioni Cavi Cable Range [mm <sup>2</sup> ]	Rif. Ordine Ordering Info	Variante Armatura Armouring	Variante Schermo Cable Shield	Lunghezza massima Max Length [mm]
EC GLS 89RR AR	6,35/11/12	25/70	EC GLS 1289RRAR U 070 □ □	X	W & A	500
		95/150	EC GLS 1289RRAR U 150 □ □	X	W & A	500
		185/240	EC GLS 1289RRAR U 240 □ □	X	W & A	500
		300/500	EC GLS 1289RRAR U 500 □ □	X	W & A	500
	8,7/15/17,5	35/95	EC GLS 1789RRAR U 095 □ □	X	W & A	500
		120/240	EC GLS 1789RRAR U 240 □ □	X	W & A	500
		300/500	EC GLS 1789RRAR U 500 □ □	X	W & A	500
	12/20/24	25/95	EC GLS 2489RRAR U 095 □ □	X	W & A	600
		120/240	EC GLS 2489RRAR U 240 □ □	X	W & A	600
		300/500	EC GLS 2489RRAR U 500 □ □	X	W & A	600
	19/33/36	35/70	EC GLS 3689RRAR U 070 □ □	X	W & A	700
		95/185	EC GLS 3689RRAR U 185 □ □	X	W & A	700
240/500		EC GLS 3689RRAR U 500 □ □	X	W & A	700	