


COLD SHRINKABLE JOINTS for MV polymeric insulated cables

Joint kit for 1 core aerial type cable

The kit consists of a triple wall stress control-insulating-semiconducting cold-shrink body and of a protective body. The bodies are supplied assembled onto removable support.

CENELEC HD 629.1 S2, CEI 20-62/1



List of kits available for use with crimp and mechanical connectors. Connectors not included.

Famiglia Prodotti Type	Tensioni Voltage U ₀ /U/U _{max} [kV]	Sezioni Cavi Cable Range [mm ²]	Rif. Ordine Ordering Info	Variante Armatura Armouring	Variante Schermo Cable Shield	Lunghezza Length [mm]
EC GLS 72	12/20/24	50/70	EC GLS 2472 U 070 □ □	X	A	700
		70/185	EC GLS 2472 U 185 □ □	X	A	700
		240/400	EC GLS 2472 U 400 □ □	X	A	750
		500/630	EC GLS 2472 U 630 □ □	X	A	800
	19/33/36	50/70	EC GLS 3672 U 070 □ □	X	A	700
		95/240	EC GLS 3672 U 240 □ □	X	A	700
		300	EC GLS 3672 U 300 □ □	X	A	750
		400/500	EC GLS 3672 U 500 □ □	X	A	800